SAGE: Software for Algebra and Geometry Experimentation

William Stein

February 26, 2006



Reminders!!

1. Turn on my iRiver recorder.

2. Thank the organizers! Lauter and Klassen.

3. I'm originally from the Northwest (Oregon), and I'm moving here next month.

向下 イヨト イヨト

The SAGE Mailing List on Thursday, Feb 2, 2006

Dear SAGE community.

My name is Tiziano and I'm from Italy. I'm writing this mail first of all because I would like to thank you all for SAGE. It's something the world was really missing.

[Every free computer algebra system I've tried has] **"reinvented** many times the wheel without being able to build the car."

Goal of SAGE: Build the car.





Another Email...

Dear William,

[...] I think that you are doing a superb work with Sage, and thank you for it.

Best,

Henri [Cohen (GP/PARI founder)]



A B K A B K

My Story

- 1997-98: Hecke and interpreter in C++ (based on other code); for modular forms research with Buzzard and Mazur.
- 1998: D. Kohel: "too bad you have to write interpreter"; vast amount of Magma code
- ▶ 1998: A. Steel: 2 days in Berkeley teaching me Magma
- ▶ 1999-2004: I wrote heaps of Magma code (3 Sydney visits), and tried to convert everyone I met to using it.
- 2000: M. Stoll "Magma Everything under one roof"
- 2004: Frustration: Magma is closed source, closed development model, and expensive; authorship issues; no user-defined objects; hard to save/load data (no eval command) – not a mainstream programming language.

・ロン ・回 と ・ヨン ・ヨン

- **S. Hillion** (Berkeley) Love using Python in my job.
- Nov 2004: Gonzalo Tornaria (Austin) "if I come up with a new algorithm what should I implement it in?"
- Jan 2005: D. Joyner winter AMS meeting; SAGE born
- One year of work with many people: David Kohel, David Joyner, Iftikhar Burhanuddin, John Cremona, Martin Albrecht, Wilson Cheung, Alex Clemesha, Neal Harris, Naqi Jaffery, David Kirkby, Jon Hanke, Gregg Musiker, Kyle Schalm, Steven Sivek, Justin Walker, Mark Watkins, Joe Wetherell, Karim Belebas, John Tate, and many others...
- ▶ Feb 4–5: SAGE Days at UCSD
- Many more contributors now! Gonzalo Tornaria, Kiran Kedlaya, Justin Walker, Steve Linton, ... and I'm getting new code (and offers of support) from people I've never heard of constantly.

イロト 不得下 イヨト イヨト

-

SAGE Days 2006



・ロト ・回ト ・ヨト ・ヨト

2

SAGE Has **3** Distinct Complementary Goals

- 1. **Distribution** of free open source mathematics software.
- 2. New computer algebra system (very structural like Gap and Magma; object-oriented; user extensible; do things right).
- 3. Better way to use all your favorite (commercial or free) mathematics software *together*.

1. Distribution of Free Open Source Software

- Free self-contained distribution of the very best open source math software that has an *active* community.
- SAGE tarball: about 40MB; all GPL or compatible; you can change anything, rebuild, make any changed versions available, can fork SAGE and make your own variant.
- Type sage -sdist <version> to make distro from your local modified version of sage. Type sage -bdist <version> to make a binary.

・ 同 ト ・ ヨ ト ・ ヨ ト

Does Open Source Matter for Math Research?

"You can read Sylow's Theorem and its proof in Huppert's book in the library [...] then you can use Sylow's Theorem for the rest of your life free of charge, but for many computer algebra systems license fees have to be paid regularly [...]. You press buttons and you get answers in the same way as you get the bright pictures from your television set but you cannot control how they were made in either case.

With this situation two of the most basic rules of conduct in mathematics are violated: In mathematics information is passed on free of charge and everything is laid open for checking. Not applying these rules to computer algebra systems that are made for mathematical research [...] means moving in a most undesirable direction. Most important: Can we expect somebody to believe a result of a program that he is not allowed to see? "

- J. Neubüser in **1993** (he started GAP in 1986).

The SAGE Website

Online Calculator			Search
		(Google the SAC	E website)
5	SAGE 1.0.0	Enterprised in	
	Software for Algebra and Geometry Experimentation		
20x	By MANY CONTRIBUTORS	2	
	Try SAGE via the web		Car Caracan
	SAGE Days 2006: First Annual Workshop		

Download	Documentation
Community (mailing lists, projects, etc.)	Components

SACF is free and onen coffmare that sunnorts research and teaching in alaebra

・ロン ・回 と ・ ヨ と ・ ヨ と

Not-included With SAGE and Why

- 1. **NZMATH** provides inspiration (but not included)
- Macaulay2 supported but not included; working with Dan Grayson right now to make it part of SAGE.
- Gnuplot screwy license (e.g., I wanted to change C source so paths not hard coded, but this is not allowed!)
- 4. KASH closed source (but FREE and very powerful)
- 5. Magma expensive and closed source (the dominant system in arithmetic geometry)
- 6. Mathematica / Maple expensive and closed source
- 7. **MATLAB** not supported, since I don't have it.

But **using these** from SAGE is supported!

2. A New Computer Algebra System

\$ ls

algebras	databases	initpy	modular	schemes
all.py	edu	interfaces	modules	sets
categories	ext	libs	monoids	structure
coding	functions	matrix	plot	tests
crypto	groups	misc	rings	version.py

\$ cat */*.py */*/*.py */*.pyx */*/*.pyx |sort|uniq|wc -1
52764

\$ cat */*.py */*.pyx */*.pyx */*.pyx |sort|uniq|grep "sa 5888 <----- INPUT TEST CODE</pre>

| ▲ 同 ▶ ▲ 臣 ▶ ▲ 臣 ▶ ○ 臣 ○ の Q ()

3. Cooperation – "Everything Under One Roof"

SAGE has many interfaces (**bold included** with SAGE):

- GAP groups, discrete math
- Singular polynomial computation
- PARI/GP number theory
- Maxima symbolic manipulation
- mwrank, ec, simon, sea elliptic curves
- ► Macaulay2 commutative algebra (e.g., over Z)
- Gnuplot 2d and 3d graphics
- KANT/KASH very sophisticated algebraic number theory
- Magma vast high-quality research math environment
- Maple symbolic, educational
- Mathematica symbolic, numerical, educational
- Octave numerical

・ 同 ト ・ ヨ ト ・ ヨ ト

$-2006 = -1 \cdot 2 \cdot 17 \cdot 59$

```
sage: (-2006).factor()
-1 * 2 * 17 * 59
sage: gap(-2006).FactorsInt()
[-2, 17, 59]
sage: pari(-2006).factor()
[-1, 1; 2, 1; 17, 1; 59, 1]
sage: maxima(-2006).factor()
-2*17*59
sage: kash(-2006).Factorization()
[ <2, 1>, <17, 1>, <59, 1> ], extended by: ext1 := -1
sage: magma(-2006).Factorization()
[ <2, 1>, <17, 1>, <59, 1> ]
sage: maple(-2006).ifactor()
-``(2)*``(17)*``(59)
sage: mathematica(-2006).FactorInteger()
\{\{-1, 1\}, \{2, 1\}, \{17, 1\}, \{59, 1\}\}
```

(本間)) ((注)) ((注)) ((注)

Non-math SAGE Components

- 1. IPython: Wonderful Interactive Shell
- 2. **Python**: A **Mainstream** Programming Language (many books; numerous excellent tutorials; constantly being improved by dozens of developers)
- 3. Pyrex: Compiled Python-Like Extension Language
- 4. Saving and Loading Objects (ZODB and cPickle)

向下 イヨト イヨト

1. IPython: Wonderful Interactive Shell




Under very active development (especially parallel version); widely used by applied math/physics people.

2. Python: A Mainstream Programming Language

- ▶ 1991: Guido van Rossum-Dutchman (now at Google)
- Numerous libraries available for networking, graphics, video game programming, numerical analysis, etc.
- Designed to be a gluing language (unlike many languages), i.e., easier to use code from other languages.
- ▶ Easy to read other people's code (unlike, e.g., Perl, C++)
- Free and open source (unlike, e.g., Java)
- From Python Advocacy FAQ:
 - Run Web sites
 - Write GUI interfaces
 - Control number-crunching code on supercomputers
 - Build test suites for C or Java code

(日) (同) (E) (E) (E)



Guido van Rossum

William Stein SAGE: Software for Algebra and Geometry Experimentation

◆□→ ◆□→ ◆注→ ◆注→ □注□

3. Pyrex: Compiled Python-Like Extension Language

```
def factorial(n):
    cdef mpz_t f
    cdef int i
    cdef char* s
    mpz_init(f)
    mpz_set_si(f, n)
    for i from 2 \le i \le n:
        mpz_mul_si(f, f, i)
    s = mpz_get_str(NULL, 32, f)
    r = int(s.32)
    free(s)
    return r
```

イロト イポト イヨト イヨト

Pyrex is CRUCIAL to Success of SAGE

- 1. Written by **Greg Ewing** of New Zealand.
- 2. Code converted to C code that is **compiled by a C compiler**.
- 3. Can use any Python functions and objects from Pyrex and any C libraries.
- 4. **Time-critical SAGE** code gets implemented in Pyrex, which is (as fast as) C code, but easier to read (e.g., since all variables and scopes are explicit).

- 4 回 ト 4 ヨ ト 4 ヨ ト

Pyrex Works

```
sage: time n=factorial_pure_python(100000)
CPU times: user 78.72 s, sys: 2.64 s, total: 81.37 s
sage: time v=pari('prod(n=1,100000,n)')
CPU times: user 18.89 s, sys: 0.19 s, total: 19.08 s
sage: time n=factorial_ZZ(100000)
CPU times: user 8.56 s, sys: 2.22 s, total: 10.79 s
magma: time n := Factorial(100000);  # MAGMA V2.12-10
Time: 9.030
sage: time n = factorial(100000)  # Pyrex (first try)
CPU times: user 6.93 s, sys: 0.00 s, total: 6.93 s
```

```
(PARI/MAGMA tricks...)
sage: time n = pari('100000!')
CPU times: user 1.06 s, sys: 0.03 s, total: 1.08 s
magma: time n := &*[1..100000];  #
Time: 0.850
```

◆□▶ ◆□▶ ◆目▶ ◆目▶ ◆□ ● ● ●

4. Saving and Loading Objects

Almost any individual object in SAGE can easily be loaded and saved in a compressed format, as can sessions. This requires almost **no programmer support**, even for very complicated objects.

```
sage: E = EllipticCurve([1,2,3,4,5])
sage: time v = E.anlist(10<sup>5</sup>)
CPU times: user 1.03 s, sys: 0.22 s, total: 1.25 s
Wall time: 1.59
sage: E.save('E')
sage: quit
Exiting SAGE (CPU time Om1.45s, Wall time Om25.36s).
$ sage
sage: F = load('E')
sage: time v = F.anlist(10<sup>5</sup>)
CPU times: user 0.00 s, sys: 0.00 s, total: 0.00 s
sage: save_session, load_session, ...
```

Help System

- function? gives documentation about function (extracted from source code)
- 2. function?? gives the **source code** of function
- 3. Because Python is so readable, function?? is incredibly useful and users frequently use it.
- 4. help(module or object) gives man-page like docs
- 5. TO DO: full text search (Steven Sivek?)

向下 イヨト イヨト

Attribution

- Whenever possible, files, function docs, and the reference manual state clearly who the author is.
- All new code submitted to SAGE must be under a GPL compatible license. Author may optionally keep copyright.
- Citation: William Stein and David Joyner, SAGE: System for algebra and geometry experimentation, Communications in Computer Algebra (SIGSAM Bulletin) (July 2005), http://sage.sourceforge.net/.
- VERY Important! Always cite the underlying backends used by SAGE for your work, e.g., GAP, Singular, PARI, Kash, etc. Ask in SAGE forum and/or use function?? to view source.

・ 同 ト ・ ヨ ト ・ ヨ ト

Example 1: Bernoulli Numbers

Easy to compare timings in different systems...

<pre>sage: a = maple('bernoulli(1000)')</pre>	# Wall	time:	9.27
<pre>sage: a = maxima('bern(1000)')</pre>	# Wall	time:	5.49
<pre>sage: a = magma('Bernoulli(1000)')</pre>	# Wall	time:	2.58
<pre>sage: a = gap('Bernoulli(1000)')</pre>	# Wall	time:	5.92
<pre>sage: a = mathematica('BernoulliB[1000</pre>) #W	time:	1.01
calcbn (http://www.bernoulli.org)	#	Time:	0.06
<pre>sage: a = gp('bernfrac(1000)')</pre>	# Wall	time:	0.00?!


The above led to a paper I'm writing with Kevin McGown.

(NOTE: Mathematica 5.2 is much faster than Mathematica 5.1 at computing Bernoulli numbers, and the timing is almost identical to PARI (for n > 1000), though amusingly Mathematica 5.2 is *slow* for $n \le 1000$!)

向下 イヨト イヨト


Example 2: Elliptic Curves L-series


sage: E = EllipticCurve('37a'); E
Elliptic Curve defined by y² + y = x³ - x over Rational H
sage: E.Lseries(1.1) --> 0.032330449021518493
sage: E.Lseries(1) --> 0.0000000000000000
sage: plot([float(E.Lseries(float(n)/20)) for n in range(10
sage: L = EllipticCurve('389a').Lseries
sage: plot([float(L(float(n)/20)) for n in range(10,30)])



William Stein SAGE: Software for Algebra and Geometry Experimentation

Example 2 (continued): Complex *L*-series





William Stein SAGE: Software for Algebra and Geometry Experimentation

Example 3: Birch and Swinnerton-Dyer

イロト イポト イヨト イヨト

2

Summary: Cool Features of SAGE

- 1. Mainstream programming language
- 2. Save and load individual data and sessions
- 3. DVI and HTML logging
- 4. Easy-to-use **compiled** extension language (can easily use C libraries).
- 5. attach, load; even works with compiled code.
- 6. All examples in documentation tested

向下 イヨト イヨト

To Do

MUCH is left to do. I hope **YOU** will help!

- 1. Much **new code** still needs to be written for plotting, algebraic geometry, linear algebra, number theory, etc., especially when no open source implementations exist.
- 2. **Optimization** parts of SAGE are currently very slow.
- 3. Many excellent **free packages** need to be included, e.g., genus2reduction, sympow, Rubinstein's L-functions package.
- 4. **Documentation!** Examples! More Documentation! Even more examples!
- 5. **Package Distribution:** rpm, msi, deb, pkg, etc. Need user support. The sage-mindist-*.*.tar package is supposed to make this easier.
- 6. **STR: Sage Technical Reports:** (Unusual?) Journal; refereed, widely mirrored, subsequent traditional journal publication.